

Safe Routes to Schools Improvement Plan Gardner Bullis Elementary School Los Altos Hills, CA

School Safety Assessment held February 2021

Fremont Rd and La Paloma Rd*
1a. Install transverse crosswalk across La Paloma Rd

Fremont Rd and Manuella Rd*
2a. Refresh crosswalk striping on both legs of intersection
2b. Increase density of continental stripes for higher visibility

- Fremont Rd and Fremont Pines Ln*
 3a. Refresh crosswalk markings
 3b. Add additional RRFB signage for back-to-back signs
 3c. Increase density of continental stripes for higher visibility across Fremont Rd
- 3d. Consider construction of a raised crossing or installation of in-road flashers
- School driveway*

- 4a. Construct curb ramps
 4b. Install crosswalks at both school driveways, including a pedestrian refuge
 4c. Add stop pavement marking and advance stop bar
 4d. Install "Turning Vehicles Yield to Bikes and Pedestrians"

Edith Rd at Adobe Bridge crossing
5a. Add green paint on bike lane to increase visibility around

Edith Rd and Foothill Expy (inset)
6a. Install hardened centerline on Edith and signage to make University Ave right-in/right-out only
6b. Install crosswalk with curb extensions across University Ave
6c. Make all crosswalks across free right slip lanes high-

- 6d. Add "Turning Vehicles Yield to Bikes and Pedestrians" signage
 6e. Install advance stop bar
 6f. Expand pedestriahn refuge islands
 6g. Install leading pedestrian intervals on all signals
 6h. Close free right from Los Altos Ave onto Edith
 6i. Close free right from 1st Ave onto Edith

continued

NOTES:

1) The above items are recommendations only and based on Safe Routes to Schools site assessment best practices. Feasibility determination, final design, accessibility, funding, and implementation of any recommended improvements is the responsibility of the appropriate governing agency.

2) Red curb and/or parking restriction signage should be provided between advance stop/yield markings and the crosswalk. Exact red curb distance should be determined in accordance with the CA-MUTCD and City policies/standards.

*Recommendations are located within Los Altos Hills

300 ft 600 ft







continued from previous page

7 Edith Rd and 2nd St (inset)
7a. Construct curb ramps
7b. Install RRFB

8a. Install RRFB

General Recommendations

- Conduct ADA Ramp Assessment
- Conduct sign audit to ensure all signs are current
- Add yellow reflector bands to all school signs